

## Dstar User Registration Process

Surf to dstarusers and select a gateway to register with.

<http://dsync.dstarusers.org/GW2Status.pl>

or go direct to VA7ICM

<https://142.179.95.92/Dstar.do>

Register your user

### ***New user?***

Register here for D-STAR access.  
Registering takes just a few seconds, and  
you won't have to enter your personal information  
again the next time you visit here.

Register

You have to wait for the Admin to license you. This usually happens within 24 hours.

You may not get an automatic email from the server.

Notes for the admin. If a user is deleted and tries to re-register there will be an error saying the callsign is already registered when you try to license the user if you don't wait for the deletion to propagate to the trust server and back.

Once you are registered you will be able to Login

### ***Already registered?***

Login with Callsign and Password.  
Please note that Callsign and Password are case sensitive!  
Callsign must be in Upper Case!

CallSign :   
Password :

Login

You will see a listing of all registered users.



SEARCH RESULT: 13 Results

Callsign	Name
K17IL	Dean Parks
KH0H	Brian Lawler
KP2X	Jim Elston
OZ1BGJ	Michael Jensen (d-star.dk)
VA7GJ	Gordon Dick
VA7ICM	VA7ICM
VA7SOL	Sol Lancashire
VA7BY	Dorothy Ong
VE7AFC	Ed Sebulsky
VE7FEY	Gord Dick
VE7FEY	Marissa Dick

Callsign  Filter

To make calls out of the gateway at least 1 ip must be assigned to your callsign for routing to work.

Go to the personal information tab and check the box to the left of the 1:, Put a space in the initial box, and put your callsign in lower case in the pcname field, and click update.

Login : VA7SOL

Please, edit after making a left check box on.

Name : Sol Lancashire

E-mail : sol@lanacs.ca

Password :

Password Confirm :

If the station has multiple radios, Target CS are distinguished by initial(last character) of a space or a capital english letter.

Definition character as follows..... (G)is a gateway. (S)is a local server.

Usually RPT(Repeater) isn't checked, initalia AreaRPT CS is the port A of ZoneRPT CS.

If RPT is checked, AreaRPT CS is the same as Target CS.

	Initial	RPT	local IP	pcname	Del
<input checked="" type="checkbox"/>	1: VA7SOL	<input type="checkbox"/>	10.234.90.32	va7sol	
<input type="checkbox"/>	2: VA7SOL	<input type="checkbox"/>	10.234.90.33		
<input type="checkbox"/>	3: VA7SOL	<input type="checkbox"/>	10.234.90.34		
<input type="checkbox"/>	4: VA7SOL	<input type="checkbox"/>	10.234.90.35		
<input type="checkbox"/>	5: VA7SOL	<input type="checkbox"/>	10.234.90.36		
<input type="checkbox"/>	6: VA7SOL	<input type="checkbox"/>	10.234.90.37		
<input type="checkbox"/>	7: VA7SOL	<input type="checkbox"/>	10.234.90.38		
<input type="checkbox"/>	8: VA7SOL	<input type="checkbox"/>	10.234.90.39		

Check item and change a set value.  
Click the Update button.

You can check the terminal information page to confirm.

Target CS <input type="text"/>	AreaRPT CS <input type="text"/>	ZoneRPT CS <input type="text" value="VA7ICM"/>	<input type="button" value="Filter"/>
--------------------------------	---------------------------------	--	---------------------------------------

**SEARCH RESULT: 13 Results**

Target CS	AreaRPT CS	ZoneRPT CS	Receive Time (UTC)	PC Name	Local IP
KP2X	VA7ICH C	VA7ICH	2008-04-20 21:36:22	kp2x	10.81.99.224
VA7GJ	VA7ICH A	VA7ICH	1970-01-01 00:00:00	va7gj	10.30.49.56
VA7ICH A	VA7ICH A	VA7ICH	1970-01-01 00:00:00	va7icm-23cm-voice	10.243.229.224
VA7ICH B	VA7ICH B	VA7ICH	1970-01-01 00:00:00	va7icm-uhf-voice	10.243.229.225
VA7ICH C	VA7ICH C	VA7ICH	1970-01-01 00:00:00	va7icm-vhf-voice	10.243.229.226
VA7ICH S	VA7ICH S	VA7ICH	2008-04-20 21:52:16	va7icm-server	10.243.229.227
VA7SOL	VA7ICH C	VA7ICH	2008-04-20 21:45:46	va7sol	10.234.90.33
VA7SOL P	VA7ICH A	VA7ICH	1970-01-01 00:00:00	va7sol-portable	10.234.90.32
VA7SXY	VA7ICH A	VA7ICH	1970-01-01 00:00:00	va7sxy	10.7.7.192
VE7AFC	VA7ICH A	VA7ICH	1970-01-01 00:00:00	ve7afc	10.217.125.152
VA7SOL	VA7ICH C	VA7ICH	2008-04-20 21:47:14	va7sol	10.234.90.33

You may also want to add other pcnames for special purpose stations. Each callsign can have upto 8 modifiers that are stored separately in the database.

	Initial	RPT	local IP	pcname	Del
<input type="checkbox"/>	1:	VA7SOL	10.234.90.32	va7sol	<input type="checkbox"/>
<input checked="" type="checkbox"/>	2:	VA7SOL <input type="text" value="D"/>	<input type="checkbox"/> 10.234.90.33	va7sol-id1-data	
<input checked="" type="checkbox"/>	3:	VA7SOL <input type="text" value="M"/>	<input type="checkbox"/> 10.234.90.34	va7sol-location-reporting	
<input type="checkbox"/>	4:	VA7SOL <input type="text"/>	<input type="checkbox"/> 10.234.90.35		